

NAG C Library Function Document

nag_rngs_corr_matrix (g05qbc)

1 Purpose

nag_rngs_corr_matrix (g05qbc) generates a random correlation matrix with given eigenvalues.

2 Specification

```
void nag_rngs_corr_matrix (Nag_OrderType order, Integer n, const double d[],
                           double c[], Integer pdc, double eps, Integer igen, Integer iseed[],
                           NagError *fail)
```

3 Description

Given n eigenvalues, $\lambda_1, \lambda_2, \dots, \lambda_n$, such that

$$\sum_{i=1}^n \lambda_i = n$$

and

$$\lambda_i \geq 0, \quad i = 1, 2, \dots, n,$$

nag_rngs_corr_matrix (g05qbc) will generate a random correlation matrix, C , of dimension n , with eigenvalues $\lambda_1, \lambda_2, \dots, \lambda_n$.

The method used is based on that described by Lin and Bendel (1985). Let D be the diagonal matrix with values $\lambda_1, \lambda_2, \dots, \lambda_n$ and let A be a random orthogonal matrix generated by nag_rngs_orthog_matrix (g05qac) then the matrix $C_0 = ADA^T$ is a random covariance matrix with eigenvalues $\lambda_1, \lambda_2, \dots, \lambda_n$. The matrix C_0 is transformed into a correlation matrix by means of $n - 1$ elementary rotation matrices P_i such that $C = P_{n-1}P_{n-2}\dots P_1C_0P_1^T\dots P_{n-2}^TP_{n-1}^T$. The restriction on the sum of eigenvalues implies that for any diagonal element of $C_0 > 1$, there is another diagonal element < 1 . The P_i are constructed from such pairs, chosen at random, to produce a unit diagonal element corresponding to the first element. This is repeated until all diagonal elements are 1 to within a given tolerance ϵ .

The randomness of C should be interpreted only to the extent that A is a random orthogonal matrix and C is computed from A using the P_i which are chosen as arbitrarily as possible.

One of the initialisation functions nag_rngs_init_repeatable (g05kbc) (for a repeatable sequence if computed sequentially) or nag_rngs_init_nonrepeatable (g05kcc) (for a non-repeatable sequence) must be called prior to the first call to nag_rngs_corr_matrix (g05qbc).

4 References

Lin S P and Bendel R B (1985) Algorithm AS213: Generation of population correlation on matrices with specified eigenvalues *Appl. Statist.* **34** 193–198

5 Parameters

1: **order** – Nag_OrderType *Input*

On entry: the **order** parameter specifies the two-dimensional storage scheme being used, i.e., row-major ordering or column-major ordering. C language defined storage is specified by **order** = Nag_RowMajor. See Section 2.2.1.4 of the Essential Introduction for a more detailed explanation of the use of this parameter.

Constraint: **order** = Nag_RowMajor or Nag_ColMajor.

2:	n – Integer	<i>Input</i>
<i>On entry:</i> the dimension of the correlation matrix to be generated, n .		
<i>Constraint:</i> $n \geq 1$.		
3:	d[n] – const double	<i>Input</i>
<i>On entry:</i> the n eigenvalues, λ_i , for $i = 1, 2, \dots, n$.		
<i>Constraints:</i>		
$\mathbf{d}[i] \geq 0.0$ for $i = 0, 1, \dots, n - 1$; $\sum_{i=1}^n \mathbf{d}[i] = n$ to within eps .		
4:	c[dim] – double	<i>Output</i>
Note: the dimension, dim , of the array c must be at least pdc \times n .		
If order = Nag_ColMajor , the (i, j) th element of the matrix C is stored in c [($j - 1$) \times pdc + $i - 1$] and if order = Nag_RowMajor , the (i, j) th element of the matrix C is stored in c [($i - 1$) \times pdc + $j - 1$].		
<i>On exit:</i> a random correlation matrix, C , of dimension n .		
5:	pdc – Integer	<i>Input</i>
<i>On entry:</i> the stride separating matrix row or column elements (depending on the value of order) in the array c .		
<i>Constraint:</i> pdc $\geq n$.		
6:	eps – double	<i>Input</i>
<i>On entry:</i> the maximum acceptable error in the diagonal elements, ϵ .		
<i>Constraint:</i> eps $\geq n \times$ machine precision .		
<i>Suggested value:</i> eps =0.00001.		
7:	igen – Integer	<i>Input</i>
<i>On entry:</i> must contain the identification number for the generator to be used to return a pseudo-random number and should remain unchanged following initialisation by a prior call to one of the functions nag_rngs_init_repeatable (g05kbc) or nag_rngs_init_nonrepeatable (g05kcc).		
8:	iseed[4] – Integer	<i>Input/Output</i>
<i>On entry:</i> contains values which define the current state of the selected generator.		
<i>On exit:</i> contains updated values defining the new state of the selected generator.		
9:	fail – NagError *	<i>Input/Output</i>
The NAG error parameter (see the Essential Introduction).		

6 Error Indicators and Warnings

NE_INT

On entry, **n** = $\langle value \rangle$.
 Constraint: **n** ≥ 1 .

On entry, **pdc** = $\langle value \rangle$.
 Constraint: **pdc** > 0 .

NE_INT_2

On entry, **pdc** = $\langle value \rangle$, **n** = $\langle value \rangle$.
 Constraint: **pdc** \geq **n**.

NE_DIAG_ELEMENTS

Diagonals of returned matrix are not unity.

NE_EIGVAL_SUM

On entry, the eigenvalues do not sum to **n**.

NE_NEGATIVE_EIGVAL

On entry, an eigenvalue is negative.

NE_REAL

On entry, **eps** < **n** \times *machine precision*: **eps** = $\langle value \rangle$.

NE_ALLOC_FAIL

Memory allocation failed.

NE_BAD_PARAM

On entry, parameter $\langle value \rangle$ had an illegal value.

NE_INTERNAL_ERROR

An internal error has occurred in this function. Check the function call and any array sizes. If the call is correct then please consult NAG for assistance.

7 Accuracy

The maximum error in a diagonal element is given by **eps**.

8 Further Comments

The time taken by nag_rngs_corr_matrix (g05qbc) is approximately proportional to n^2 .

9 Example

Following initialisation of the pseudo-random number generator by a call to nag_rngs_init_repeatable (g05kbc), a 3 by 3 correlation matrix with eigenvalues of 0.7, 0.9 and 1.4 is generated and printed.

9.1 Program Text

```
/* nag_rngs_corr_matrix(g05qbc) Example Program.
 *
 * Copyright 2001 Numerical Algorithms Group.
 *
 * Mark 7, 2001.
 */

#include <stdio.h>
#include <nag.h>
#include <nag_stdl�.h>
#include <nagg05.h>

int main(void)
{
    /* Scalars */
    double eps;
```

```

Integer i, igen, j, n;
Integer exit_status=0;
Integer pdc;
NagError fail;
Nag_OrderType order;

/* Arrays */
double *c=0, *d=0;
Integer iseed[4];

#ifndef NAG_COLUMN_MAJOR
#define C(I,J) c[(J-1)*pdc + I - 1]
    order = Nag_ColMajor;
#else
#define C(I,J) c[(I-1)*pdc + J - 1]
    order = Nag_RowMajor;
#endif

INIT_FAIL(fail);
Vprintf("g05qbc Example Program Results\n\n");

/* Skip heading in data file */
Vscanf("%*[^\n] ");
Vscanf("%ld%*[^\n] ", &n);

/* Allocate memory */
if ( !(c = NAG_ALLOC(10 * 10, double)) ||
     !(d = NAG_ALLOC(10, double)) )
{
    Vprintf("Allocation failure\n");
    exit_status = -1;
    goto END;
}

#ifndef NAG_COLUMN_MAJOR
    pdc = n;
#else
    pdc = n;
#endif

if (n <= 10)
{
    for (i = 0; i < n; ++i)
    {
        Vscanf("%lf", &d[i]);
    }
    Vscanf("%*[^\n] ");

    eps = 1e-4;

    /* igen identifies the stream. */
    igen = 1;
    /* Initialise the seed to a repeatable sequence */
    iseed[0] = 1762543;
    iseed[1] = 9324783;
    iseed[2] = 423446;
    iseed[3] = 742355;

    g05kbc(&igen, iseed);

    g05qbc(order, n, d, c, pdc, eps, igen, iseed, &fail);
    if (fail.code != NE_NOERROR)
    {
        Vprintf("Error from g05qbc.\n%s\n", fail.message);
        exit_status = 1;
        goto END;
    }
    for (i = 1; i <= n; ++i)
    {
        for (j = 1; j <= n; ++j)

```

```

    {
        Vprintf("%9.3f%s", C(i,j), j%3 == 0 || j == n ?"\n":" ");
    }
END:
if (c) NAG_FREE(c);
if (d) NAG_FREE(d);
return exit_status;
}

```

9.2 Program Data

None.

9.3 Program Results

g05qbc Example Program Results

1.000	0.204	-0.106
0.204	1.000	-0.278
-0.106	-0.278	1.000
